■ Waste Disposal by Landfill Plan

- Currently, it is strongly demanded that landfill sites be used for as long as possible.
- The Tokyo Metropolitan Government has formulated the Plan for Waste Disposal by Landfill and is systematically advancing the construction of landfills.
- The Plan for Waste Disposal by Landfill will be reviewed every five years.

Waste Disposal by Landfill Plan (Revised February 2022) (Plan period : 15 years from FY 2022 to 2036) Unit: Ten thousand m

Tracto Diopodal by Laridini Flam (Noviced February 2022) (Flam period : To years from 1 1 2022 to 2000)										
	Fiscal Year	2022 - 2026					2027 2024	2022 2026	2022-2036	
riscal real		2022	2023	2024	2025	2026	Subtotal	2027-2031	2032-2036	Total
\$	General Waste(%)	22	20	20	19	18	99	84	77	260
Waste	Industrial Waste	8	8	8	8	8	40	40	40	120
Туре	Waste from Public Facilities	16	15	14	14	14	72	70	70	212
Эе	Subtotal	46	43	42	41	40	211	194	187	592
Earth Sand	Dredged Soil	89	89	89	89	89	445	435	435	1,315
id th Ja	Soil Produced in Construction Work, etc.	30	30	30	30	30	150	150	150	450
and Type	Subtotal	119	119	119	119	119	595	585	585	1,765
Total		165	162	161	160	159	806	779	772	2,357

^{*}The volume of waste soil covering, etc., is included in general waste.

The type of waste and policy for acceptance of waste at the Shinkaimen Landfill Site are determined in the Plan for Waste Disposal by Landfill.


Waste Acceptance Policy by Type of Waste

	waste Acceptance Policy by Type of Waste						
	Type of Waste		Acceptance Policy				
Waste Type	Wa	General Waste	 General waste produced by households, etc. within the 23 wards of Tokyo. All waste is accepted provided that it undergoes intermediate treatment, while efforts are also undertaken to reduce waste volume and maximize the reuse and recycling of resources. 				
	aste Ty	Industrial Waste	•Industrial waste produced by small and medium-sized businesses within Metropolitan Tokyo. •Waste that has already undergone intermediate treatment is accepted up to a fixed volume.				
	pe	Waste from Public Facilities	•Waste produced from waterworks and sewage facilities within Metropolitan Tokyo. •Waste is accepted provided that it undergoes intermediate processing.				
Earth Sand	Earth Sand	Dredged Soil	•Dredged soil is produced from streams and rivers within Metropolitan Tokyo and Tokyo ports. •Dredged soil that cannot be used for the upkeep of rivers, canals or harbors is accepted.				
	and Type	Soil Produced in Construction Work, etc.	•This soil is used for upkeep of the landfill site and as soil covering for waste.				

Background

Month/Year	
November/1989	Request made to the Tokyo Port and Harbor Council to conduct a study on a basic policy for construction of a new landfill site on the water for waste disposal.
July/1991	Shinkaimen Landfill Site waste acceptance policy by type of waste and the plan for waste disposal by landfill formulated in the Long Term Vision for Waste Disposal by Landfill.
December/1991	Report by the Tokyo Port and Harbor Council on a basic policy for construction of a new landfill site on the water.
May/1992	Shinkaimen Landfill Site plan decided through partial amendment of the Port and Harbor Plan of the Port of Tokyo (Fifth Edition).
October/1993	Submission of the Environmental Impact Assessment (tentative) based on the Tokyo Metropolitan Government Environmental Impact Assessment Ordinance and Guidelines for Implementation of Environmental Impact Assessment (Cabinet decision).
October/1994	Completion of environmental impact assessment procedures.
August/1995	Application for License to Reclaim Publicly-owned Water Surfaces based on the Act on Reclamation of Publicly-owned Water Surface.
July/1996	Acquisition of License to Reclaim Publicly-owned Water Surface.
May/1998	Formulation of the Plan for Waste Disposal by Landfill.
January/2003	Revision of the Plan for Waste Disposal by Landfill.
January/2006	Partial revision of the Plan for Waste Disposal by Landfill.
January/2007	Revision of the Plan for Waste Disposal by Landfill.
February/2012	Revision of the Plan for Waste Disposal by Landfill.
December/2013	Partial revision of the Plan for Waste Disposal by Landfill.
February/2017	Revision of the Plan for Waste Disposal by Landfill.
February/2022	Revision of the Plan for Waste Disposal by Landfill.

Location Map



<Materials : Bureau of Port and Harbor, Tokyo Metropolitan Government> <@ Tokyo Digital map>




Bureau of Port and Harbor, Tokyo Metropolitan Government HP http://www.kouwan.metro.tokyo.lg.jp/

8-1 Nishi-Shinjuku 2-chome, Shinjuku-ku, Tokyo 163-8001 登録番号(4)5



The last landfill site in Tokyo Bay, which supports the comfortable lives of Tokyo residents.

Shinkaimen Landfill Site



Photographed on January 2021



 $[\]mbox{\%}\mbox{Due}$ to rounding, some totals may not correspond with the sum of the separate figures.


Overview of Shinkaimen Landfill Site

In order to ensure the comfortable lives of the Tokyo residents and maintain urban dynamism, the Shinkaimen Landfill Site, which is the final waste disposal site in Tokyo Bay, will be built in stages.

Manage

A.P. around -40.0m

The landfill will be used for as long as possible through recycling and effective use of waste that will be disposed by landfill.



Gently sloping shore protection is friendly to wildlife


By establishing shallows and Tide pools on the gently sloping shore protection, habitats for marine life will be expanded.

Gently sloping outer shore protection (east side)




Tide pool at low tide (※)

(※)Tide pool: A shallow pool formed in the tidal zone, which appears at low tide and is under water at high tide. It is the prefect habitat for young fish and periphytons.




[Landfill cross-section]



Reclamation using dredged soil at the Shinkaimen Landfill Site

Shallows

• For reclamation using dreaded soil, an anti-pollution soil transporter takes dredged soil to blocks C and G.



Caisson type outer shore protection (B & C Blocks)

Outer shore protection (east side) has water

does not seep into groundwater or the ocean.

Tide pool

sealing features so that polluted water from waste


0-meter-long gently sloping revetment and shallow




How dredged soil is sent

Entry of *KAIRYU*, the ship carrying the dredged soil






- •After building the shore protection, digging of the ocean floor is conducted to incease capacity.
- •Efforts are taken to effectively use the dredged soil in building fishing grounds in Tokyo Bay.




·After filling this area with dredged soil, drains are driven in and vacuum pumps are used to extract water from the filled foundation and seabed soil to accelerate consolidation settlement to increase capacity.



· Efforts are taken to expand capacity of the landfill site such as by effectively using the accepted dredged soil after its dewatering as civil engineering materials for foundation preparation, etc,







	Construction of s	shore protection	Filling			
	Start construction	Almost completed	Start acceptance of soil	Start acceptance of waste		
A Block	August/1996	March/1997	June/1997	December/1998		
B Block	August/1996	May/1998	August/1998	February/2003		
C Block	October/1997	May/2001	March/2002			
D Block	September/2009					
G Block	December/2000	July/2012	August/2012			